

POE-UM4

UNMANAGED SMART POE SWITCH



Features:

- IEEE 802.3at PoE plus compliant to simplify deployment and installation
- IEEE 802.3x flow control protects against lost packets for reliable data transmission
- Simple Plug and Play installation
- 4 x 10/100Mbps and 4 x 10/100Mbps PoE Plus ports
- 11-inch metal housing with 19-inch rackmount kit included
- Auto-detection and protection of non-standard PoE devices

SPECIFICATION	POE-UM4
STANDARD	IEEE 802.3 10-BASE-T (Ethernet) IEEE 802.3u 100-BASE-TX (Fast Ethernet) IEEE 802.3x Flow Control (full-duplex flow control) IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus
Features	MAC Address: 1K Buffer Memory: 64KB Transmission Method: Store and Forward Backplane: 1.6Gbps
PoE Spec	PoE Standard: IEEE 802.3af/at Power over Ethernet / PSE PD classification identity PoE over current protection PoE circuit sorting protection PoE Power Output: Per Port 54V DC, Max. 15.4 watts (IEEE 802.3af) or 30 watts (IEEE 802.3at) Power Budget: Max. 61.6W Power Pin Assignment: 1/2(+), 3/6(-)
Transmission media	10 BaseT Cat 3,4,5 UTP/STP 100M BaseTx CAT 5 UTP/STP
Filtering/Forwarding Rates	100Mbps port-148,000pps 10Mbps port-14,880pps
LED Indicators	Per Port: Link/Act, PoE Act/Status Per Unit: Power
Network Interface	4 x 10/100Mbps RJ-45 PoE 1~4 Ports 4 x 10/100Mbps RJ-45 Uplink 5~8 Ports
Power Input	Input: 100~240V/AC, 50~60 Hz, 2A Internal Power Supply
Power Consumption	65Watts(Max)
Dimensions: (L x W x H) / Weight	282.2 x 178 x 44 mm / 1500g
Temperature	Operating: 0 ~ 40°C Storage: -20~70°C Humidity: 10~90%, Non-condensing
Certifications	CE/FCC

